PCT

WORLD INTELLECTUAL PROP International E



INTERNATIONAL APPLICATION PUBLISHED UNDER

WO 9607353A1

(81) Designated States: IP, NZ, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).

(51) International Patent Classification ⁶: A61B 6/04, A47C 21/04

A1

(11) International Publication Number:

WO 96/07353

• |

(43) International Publication Date:

14 March 1996 (14.03.96)

(21) International Application Number:

PCT/US95/11507

(22) International Filing Date:

11 September 1995 (11.09.95)

(30) Priority Data:

08/303,462

9 September 1994 (09.09.94)

Published

With international search report.

Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.

(71) Applicant: AIR-SHIELDS, INC. [US/US]; 330 Jacksonville Road, Hatboro, PA 19040 (US).

Road, Halboro, PA 19040 (US).


(72) Inventor: BARSKY, Barry, E.; 612 Anne Street, Huntingdon Valley, PA 19006 (US).

(74) Agents: NEY, Andrew, L. et al.; Ratner & Prestia, 500 North Gulph Road, P.O. Box 980, Valley Forge, PA 19482 (US).

(54) Title: INFANT MATTRESS ASSEMBLY

(57) Abstract

An infant mattress assembly which is X-ray transparent, so that an X-ray cassette can be positioned beneath the infant mattress assembly and X-ray images can be taken of an infant placed on the infant mattress assembly. The infant mattress assembly includes a mattress (10) having a top surface (12) upon which an infant can be placed, a bottom surface (14) spaced from the top surface, and an X-ray transparent cushion (10) between the top surface (12) of the mattress (10) and the bottom surface (14) of the mattress (10). This infant mattress assembly also includes an Xray transparent film heater unit (18) beneath the bottom surface (14) of the mattress (10) and in heat transfer disposition with the X-ray transparent cushion (16).



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	GB	United Kingdom	MR	Mauritania
AU -	Australia	GB	Georgia	MW	Malawi
BB	Barbados	GN '	Guinea	NE	Niger
BE	Belgium_	GR	Greece	NL	Netherlands
BF '	Burkina Faso	HU	Hungary .	NO:	Norway
BG	Bulgaria	IE	Ireiand	NZ	New Zealand
BJ	Benin	IT	Italy	PL	Poland
BR	Brazil ·	JP	Japan	PT	Portugal
BY	Belarus	KE	Kenya	RO	Romania
CA	Canada	KG	Kyrgystan	RU	Russian Federation
CF	Central African Republic	KP	Democratic People's Republic	SD	Sudan
CG	Congo		of Korea	SE ·	Sweden
CH	Switzerland	KR	Republic of Korea	SI	Slovenia
CI	Côte d'Ivoire	KZ	Kazakhstan	SK	Slovakia
CM	Cameroon	u	Liechtenstein	SN	Senegal
CN	China	LK	Sri Lanka	TD	Chad
cs	Czechoslovakia	LU	Luxembourg	TG	Togo
CZ	Czech Republic	LV	Latvia	ŤJ	Tajikistan
DE	Germany	MC	Monaco	TT	Trinidad and Tobago
DK	Denmark	MD	Republic of Moldova	ÜA	Ukraine
ES	Spain	MG	Madagascar	US	United States of Americ
FI	Finland	ML	Mali	UZ	Uzbekistan
FR	France	MN	Mongolia	· VN	Viet Nam
GA	Gabon			***	* N-C 1 (411)

20 .

25

INFANT MATTRESS ASSEMBLY

TECHNICAL FIELD

The present invention relates, in general, to the treatment of infants and, in particular, to a mattress assembly having a heated mattress which provides warmth to an infant placed upon the mattress.

BACKGROUND OF THE INVENTION

Infant incubators, body warmers, phototherapy units
and other equipment are used in the treatment and maintenance
of weak, sickly, premature and low birth weight infants.
Often, it is desirable to provide additional heat to the
infant, beyond the heat which is available from the particular
piece of equipment being employed in the treatment and
maintenance of the infant.

Typically, such equipment has a mattress upon which the infant is placed. In the past, certain of these mattresses have been arranged with resistance wire heaters and heated water containers.

It is often necessary to take X-ray images of an infant being treated, for example, in an incubator. In order to avoid disturbing the infant or sensors and instrumentation attached to the infant when an X-ray cassette is inserted directly under the body of the infant, the X-ray cassette preferably is positioned beneath the support upon which the mattress is placed and which can be lifted by a lift mechanism which is provided in most incubators. This requires that the components, namely the mattress support, the heater, and the mattress be X-ray transparent.

Resistance wire heaters are undesirable because they are not X-ray transparent and effectively preclude taking

X-ray images as described above. Heated water containers are cumbersome and awkward to handle.

SUMMARY OF THE INVENTION

Accordingly, an infant mattress assembly,

constructed in accordance with the present invention, includes
a mattress having a top surface upon which an infant can be
placed, a bottom surface spaced from the top surface, and an
X-ray transparent cushion between the top surface and the
bottom surface. This infant mattress assembly also includes
an X-ray transparent film heater unit beneath the bottom
surface of the mattress and in heat transfer disposition with
the cushion.

BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 is a sectional view of a first embodiment of an infant mattress assembly constructed in accordance with the present invention.

Figure 2 is a sectional view of the X-ray transparent film heater unit of the Figure 1 infant mattress assembly.

Figure 3 is a sectional view of a second embodiment of an infant mattress assembly constructed in accordance with the present invention.

Figure 4 is a sectional view of the X-ray transparent film heater unit and its housing of the Figure 3 infant mattress assembly.

Figure 5 is a perspective view of a third embodiment of an infant mattress assembly constructed in accordance with the present invention.

Figure 6 is a side view, partially in section, which shows the relative positions of an infant mattress assembly,

. 5

10

15

20

25

30

35

constructed in accordance with the present invention, a mattress assembly support and an X-ray cassette or a phototherapy unit.

DETAILED DESCRIPTION OF THE INVENTION

Referring to Figure 1, an infant mattress assembly, constructed in accordance with the present invention, includes a mattress 10 having a top surface 12 upon which an infant can be placed, a bottom surface 14 spaced from said top surface, and an X-ray transparent cushion 16 between top surface 12 and bottom surface 14. Also included in this infant mattress assembly is an X-ray transparent film heater unit 18 beneath bottom surface 14 of mattress 10 and in heat transfer disposition with X-ray transparent cushion 16. X-ray transparent film heater unit 18 is powered through a line cord 19.

The Figure 1 embodiment of the present invention also includes a mattress cover 20 which has an upper compartment 22 which defines top surface 12 of mattress 10 and bottom surface 14 of the mattress and within which X-ray transparent cushion 16 is positioned. Mattress cover 20 also has a lower compartment 24 within which X-ray transparent film heater unit 18 is positioned. With X-ray transparent film heater unit 18 so positioned and being flexible, it conforms to the contour of the common wall between upper compartment 22 and lower compartment 24 of mattress cover 20. X-ray transparent film heater unit 18 serves as a heat source from which heat is conducted through mattress 10 to an infant placed on the mattress.

The Figure 3 embodiment of the present invention includes a mattress cover 26 which defines top surface 28 of mattress 30 and bottom surface 32 of the mattress and within which X-ray transparent cushion 34 is positioned and a heater housing 36 within which an X-ray transparent film heater unit is positioned. The X-ray transparent film heater unit is powered through a line cord 39.

25

30

35

Preferably, X-ray transparent cushion 16 of the Figure 1 embodiment of the present invention and X-ray transparent cushion 34 of the Figure 3 embodiment of the present invention are conventional bubble-pack material arranged in two layers 40 and 42 with the fluid-filled chambers 44 of one layer fitted into spaces between the fluid-filled chambers of the other layer. Preferably, the fluid in the bubble-pack material is clean air.

As shown in Figure 2, which is a sectional view of

X-ray transparent film heater unit 18 of the Figure 1 infant
mattress assembly, the X-ray transparent film heater unit can
be composed of a laminate of a conductive material and a
dielectric substrate. For example, the X-ray transparent film
heater can be an indium tin oxide/PET laminate 46 disposed

between a pair of thick films 48 and 50 made from, for
example, PVC, PVDC or PET, with the indium tin oxide/PET
laminate adhesively bonded to upper thick film 48. X-ray
transparent film heater unit 38 of the Figures 3 and 4
embodiment of the present invention can be arranged the same
way in heater housing 36.

As shown in Figure 4, which is a sectional view of the X-ray transparent film heater unit and its housing of the Figure 3 infant mattress assembly embodiment of the present invention, housing 36 is composed of an upper panel 33, a lower panel 35 and a perimeter seal 37. Also included within heater housing 36 are means for urging X-ray transparent film heater unit 38 upward toward X-ray transparent cushion 34. As shown in Figure 4, such means preferably include bubble-pack material 50. With transparent film heater unit 38 so positioned, it serves as a heat source from which heat is conducted through upper panel 33 of housing 36 and mattress 30 to an infant placed on the mattress. While in the Figure 1 embodiment the X-ray transparent film heater is flexible, in the Figure 3 embodiment the X-ray transparent film heater can be rigid because it is contained within a rigid housing.

10

15

The management

- : -

Referring to Figure 5, which is a perspective view of a third embodiment of the present invention, X-ray transparent film heater unit 52 of the mattress assembly, powered through a line cord 53, can be arranged to extend beyond the lateral edges 54 and 56 extending along the length of mattress 58 and between top surface 60 of the mattress and bottom surface 62 of the mattress. For this arrangement, heater housing 64 and X-ray transparent film heater unit 52 within the heater housing can be generally similar to heater housing 36 and X-ray transparent film heater unit 38 of the Figures 3 and 4 embodiment of the present invention, except that in the Figure 5 embodiment the heater housing and the X-ray transparent film heater unit are flexible and are sized to extend beyond lateral edges 54 and 56 of mattress 58 to form a tunnel which surrounds an infant placed on the Suitable means, for example a zipper 66, for mattress. fastening together the lateral edges of heater housing 64, are provided at the lateral edges of the heater housing.

In the Figure 5 embodiment of the present invention,

X-ray transparent film heater unit 52 serves not only as a
heat source from which heat is conducted to the infant through
mattress 58 but also as a source of radiant heat as
represented by arrows 68. The "eye" 70 represents optical
transparency of heater housing 64 and X-ray transparent film
heater unit 52.

U.S. 5,119,467 is directed to a transparent film radiant heat source for use with infant incubators and discloses a number of constructions of a transparent film heater which can serve as the X-ray transparent film heater unit 18 of the Figures 1 and 2 embodiment of the present invention, the X-ray transparent film heater unit 38 of the Figures 3 and 4 embodiment of the present invention, and the X-ray transparent film heater unit 52 of the Figure 5 embodiment of the present invention. Accordingly, U.S. 5,119,467 is incorporated by reference herein as if its full contents were set forth herein.

30

35

10

15

20

25

30

35

Referring to Figure 6, an infant mattress assembly, constructed in accordance with any of the embodiments of the present invention which have been described and including a mattress/X-ray transparent film heater unit 72, can be positioned on a mattress assembly support 76 with an X-ray cassette, represented by reference numeral 78, positioned beneath the mattress assembly support. Mattress support 76 can have an opening 80 as shown in Figure 6, provided the housing of the X-ray transparent film heater unit is rigid (e.g. Figure 3) and can support the mattress and the infant placed on the mattress or can be solid throughout its length. provided the mattress support is X-ray transparent, in which case the mattress support provides support for the mattress and the infant placed on the mattress and the housing of the X-ray transparent film heater unit can be flexible (e.g. Figures 1 and 5).

As indicated above, it is often necessary to take X-ray images of an infant being treated in an incubator, radiant warmer, or the like. In order to avoid disturbing the infant or sensors and instrumentation attached to the infant when an X-ray cassette is inserted directly under the body of the infant, the X-ray cassette preferably is positioned beneath the mattress support upon which the infant is placed which can be lifted by a lift mechanism built into the unit in which the infant is being treated. This requires that the components (i.e. mattress support, heater unit, and mattress) be X-ray transparent. A X-ray transparent film heater, a bubble-pack layer and an X-ray transparent mattress support or a mattress support having an opening satisfy this requirement.

Although a number of materials can be used as the mattress cushion, bubble-pack material is particularly beneficial. As compared to closed-cell foam, which is a common mattress material, bubble-pack material has superior heating and heat transfer characteristics. Bubble-pack material heats up much more quickly than does closed-cell foam and the heat loss in bubble-pack material is considerably less than in closed-cell foam. As compared to reticulated foam,

bubble-pack material is considerably less expensive and X-ray artifacts are negligible.

It should be noted that, with the mattress and transparent film heater made from the materials described above, a removable phototherapy light source, also represented by reference numeral 78 in Figure 6, can be introduced beneath the mattress support because these materials also are transparent to visible light and the frequencies used in phototherapy.

While in the foregoing there have been described preferred embodiments of the present invention, it should be understood by those skilled in the art that various modifications and changes can be made without departing from the true spirit and scope of the present invention.

What is Claimed:

1.	1. An infant mattress assembly comprising:
2	a mattress having:
3	(a) a top surface upon which an infant can be
4	placed,
5	(b) a bottom surface spaced from said top surface
6	and
7	(c) an X-ray transparent cushion between said top
8	surface and said bottom surface;
9	and an X-ray transparent film heater unit beneath
10	said bottom surface of said mattress and in heat transfer
11	disposition with said X-ray transparent cushion.
1	2. An infant mattress assembly according to claim
3	1 wherein said X-ray transparent cushion is bubble-pack material.
1	3. An infant mattress assembly according to claim
2	1 wherein said X-ray transparent cushion is two layers of
3	bubble-pack material, each layer having a plurality of fluid-
4	filled chambers with the chambers of one layer fitted into
5 ·	spaces between the chambers of the other layer.
1	4. An infant mattress assembly according to claim
2	1 further including a mattress cover having:
3	(a) an upper compartment defining said top surface
4 .	of said mattress and said bottom surface of said
5	mattress and within which said X-ray transparent
6.	cushion is positioned, and
7	(b) a lower compartment within which said X-ray
8 .	transparent film heater unit is positioned.


1	5. An infant mattress assembly according to claim
2	4 wherein said X-ray transparent cushion is bubble-pack
3	material.
1	6. An infant mattress assembly according to claim
2	4 wherein said X-ray transparent cushion is two layers of
3	bubble-pack material, each layer having a plurality of
4 .	fluid-filled chambers with the chambers of one layer fitted
5	into spaces between the chambers of the other layer.
1	7. An infant mattress assembly according to claim
2	1 further including:
3	(a) a mattress cover defining said top surface of
4	said mattress and said bottom surface of said
5	mattress and within which said X-ray transparent
6	cushion is positioned, and
7. :	(b) a heater housing within which said X-ray
8	transparent film heater unit is positioned.
1	8. An infant mattress assembly according to claim
2	7 wherein said X-ray transparent cushion is bubble-pack
3	material.
1	9. An infant mattress assembly according to claim
2	7 wherein said X-ray transparent cushion is two layers of
3	bubble-pack material, each layer having a plurality of
4	fluid-filled chambers with the chambers of one layer fitted
5	into spaces between the chambers of the other layer.
1	10. An infant mattress assembly according to claim
2	1 wherein:
3 -	(a) said mattress has lateral edges extending along
4	the length thereof and between said top surface of
5	said mattress and said bottom surface of said
6	matterna and


7 .	(b) said X-ray transparent film heater unit extends
8	beyond said lateral edges of said mattress.
1	11. An infant mattress assembly according to claim
2	10 wherein said X-ray transparent cushion is bubble-pack
3	material.
1	12. An infant mattress assembly according to claim
2	10 wherein said X-ray transparent cushion is two layers of
3	bubble-pack material, each layer having a plurality of
4	fluid-filled chambers with the chambers of one layer fitted
5	into spaces between the chambers of the other layer.
1	13. An infant mattress assembly according to claim
2	7 further including means within said heater housing for
3	urging said X-ray transparent film heater unit upward toward
4	said X-ray transparent cushion.
1	14. An infant mattress assembly according to claim
2	13 wherein said urging means include bubble-pack material.
1	15. An infant mattress assembly according to claim
2	10 further including:
3	(a) a mattress cover defining said top surface of
4	said mattress and said bottom surface of said
5	mattress and within which said X-ray transparent
6	cushion is positioned, and
7	(b) a heater housing within which said X-ray
8	transparent film heater unit is positioned.
1	16. An infant mattress assembly according to claim
2	15 wherein said heater housing and said X-ray transparent film
3	heater unit are flexible.
1	17. An infant mattress assembly according to claim
2 .	16 wherein said heater housing and said X-ray transparent film

- heater unit are sized to extend beyond said lateral edges of an aid mattress to surround an infant placed on said mattress.
- 18. An infant mattress assembly according to claim
 2 17 wherein said heater housing has lateral edges extending
 3 along the length thereof and said infant mattress assembly
 4 further includes means for fastening said lateral edges of
 5 said heater housing together.
- 1 19. An infant mattress assembly according to claim 2 7 wherein said heater housing is rigid.
- 20. An infant mattress assembly according to claim 19 further including means within said heater housing for urging said X-ray transparent film heater unit upward toward said X-ray transparent cushion.
- 21. An infant mattress assembly according to claim
 2 20 wherein said urging means include bubble-pack material.
- 22. An infant mattress assembly according to claim
 the wherein said X-ray transparent film heater unit includes a
 laminate of a conductive material and a dielectric substrate.
- 23. An infant mattress assembly according to claim 4 wherein said X-ray transparent film heater unit includes a 3 laminate of a conductive material and a dielectric substrate.
- 24. An infant mattress assembly according to claim
 7 wherein said X-ray transparent film heater unit includes a
 laminate of a conductive material and a dielectric substrate.
- 25. An infant mattress assembly according to claim
 2 10 wherein said X-ray transparent film heater unit includes a
 3 laminate of a conductive material and a dielectric substrate.

1	26. An infant mattress	assembly according to claim
2.	15 wherein said X-ray transparent	film heater unit includes a
3	laminate of a conductive material	and a dielectric substrate.

- 27. An infant mattress assembly according to claim
 2 22 wherein said laminate is flexible.
- 28. An infant mattress assembly according to claim
 2 23 wherein said laminate is flexible.
- 29. An infant mattress assembly according to claim 25 wherein said laminate is flexible.





2/2





FIG. 5



SUBSTITUTE SHEET (RULE 26)

INTERNATIONAL SEARCH REPORT

Intern al Application No PCT/US 95/11507

A. CLASSI	IFICATION OF SUBJECT MATTER A61B6/04 A47C21/04		
	·		
	o International Patent Classification (IPC) or to both national classification	ication and IPC	
	SEARCHED Cocumentation searched (classification system followed by classification)	on symbols)	
IPC 6	A61B A47C		·
Documentat	tion searched other than minimum documentation to the extent that s	uch documents are included in the fields se	arched
Electronic d	lata base consulted during the international search (name of data base	e and, where practical, search terms used)	
			, ,
C. DOCUM	IENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of document, with indication, where appropriate, of the re	levant passages	Relevant to claim No.
A	FR,A,1 487 809 (USINES REY & TRAM April 1967	BLAY) 29	1
,	see page 1, left column, line 1 - see page 1, right column, line 44 2, left column, line 14 see page 3, left column, line 28	- page	•
A	FR,A,1 002 206 (W. WEBER) 4 March see the whole document		i
A.	EP,A,O 325 850 (HILL-ROM COMPANY August 1989 see abstract; claims; figures 4-9		1
A	DE,U,82 28 688 (RICHARD WOLF GMBH December 1982 see claims 1,5; figures	1) 9	1
	•	a a second	
Furt	ther documents are listed in the continuation of box C.	X Patent family members are listed i	n annex.
"A" docum consid "E" earlier filing "L" docum which citatio "O" docum other	nent defining the general state of the art which is not dered to be of particular relevance document but published on or after the international date sent which may throw doubts on priority claim(s) or is cited to establish the publication date of another on or other special reason (as specified) the perior of the special reason (as specified) the perior referring to an oral disclosure, use, exhibition or means	"T" later document published after the inter- or priority date and not in conflict with cited to understand the principle or the invention. "X" document of particular relevance; the cannot be considered novel or cannot involve an inventive step when the do. "Y" document of particular relevance; the cannot be considered to involve an indocument is combined with one or in ments, such combination being obvious in the art.	th the application but secry underlying the claimed invention be considered to current is taken alone claimed invention wentive step when the ore other such docu-
later t	ent published prior to the international filing date but than the priority date claimed	'&' document member of the same patent	
	December 1995	Date of mailing of the international se	
	mailing address of the ISA	Authorized officer	
	European Patent Office, P.B. 5818 Patentlaan 2 NL - 2280 HV Rijswijk Tel. (+31-70) 340-2040, Tx. 31 651 epo nl, Fax (+31-70) 340-3016	Fontenay, P	

Form PCT/ISA/210 (second sheet) (July 1992)

THIS PAGE BLANK (USPTO)

INTERNATIONAL SEARCH REPORT

Intern. al Application No PCT/US 95/11507

Patent document cited in search report	Publication date	Patent family member(s)		Publication date
FR-A-1487809	19-10-67	NONE		
FR-A-1002206	07-03-52	NONE		
EP-A-325850	02-08-89	US-A- CA-A- DE-A- JP-A-	4926457 1285103 3868502 2005948	15-05-90 25-06-91 26-03-92 10-01-90
 DE-U-8228688		NONE		

Form PCT/ISA/218 (patent family annex) (July 1992)

THIS PAGE BLANK (USPTO)